



RAVENOL MARINEOIL PETROL SAE 25W-40 SYNTHETIC



ART.-NR. 1162115

4 L | 1162115-004
 10 L | 1162115-010
 20 L | 1162115-020
 20 L | 1162115-B20
 1000 L | 1162115-700

VISCOSITY 25W-40

SPECIFICATIONS API SL | ACEA A3/B4

FABRICATION FULLY SYNTHETIC

RECOMMENDATIONS VETUS DEUTZ | STEYR | MTU | VOLVO | MAN |
 MERCUISER | PERKINS | NANNI DIESEL | YANMAR | DETROIT DIESEL |
 SULZER | SKL

RAVENOL MARINEOIL PETROL 25W-40 synthetic is an engine oil for the use in marine petrol engines.

RAVENOL MARINEOIL PETROL 25W-40 synthetic is produced with unconventional and HC basic oils, synthetic components and additives.

RAVENOL MARINEOIL PETROL 25W-40 synthetic guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Characteristics

RAVENOL MARINEOIL PETROL 25W-40 synthetic offers :

- excellent detergent and dispersant characteristics
- low evaporation
- high aging stability
- protection of reflecting surface formation
- very good cold start characteristics
- reduces oil and fuel consumption

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	866,0	DIN 51 757
Colour		blue	visual
Viscosity at 100°C	mm ² /s	13,7	DIN 51 562
Viscosity at 40°C	mm ² /s	92,0	DIN 51 562
Viscosity at -25°C	mPa.s	<7000	DIN 51 377
Viscosity index VI		151	DIN ISO 2909



Property	Unit	Data	Audit
Pourpoint	°C	- 36	DIN ISO 3016
Flash point (COC)	°C	214	DIN ISO 2592
TBN	mg KOH/g	11	ASTM D2896
Sulphated ash	%wt.	1,3	-

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. June 2019