



RAVENOL PDK Fluid



ART.-NR. 1211131

1 L | 1211131-001
4 L | 1211131-004
20 L | 1211131-020
20 L | 1211131-B20
1000 L | 1211131-700

FABRICATION FULLY SYNTHETIC

RECOMMENDATIONS PORSCHE PDK | PORSCHE 000 043 207 29 |
PORSCHE OIL NO. 999.917.080.00 | BMW 8322 2167 666 (MTF-LT-5) | MB
236.24 (A 002 989 04 03)

RAVENOL PDK Fluid is a fully synthetic automatic transmission oil ATF with low viscosity and with special additives and inhibition to ensure the proper operation of the automatic Transmission.

RAVENOL PDK Fluid was specially developed for Porsche Doppelkupplungsgetriebe (Dual clutch transmission). In addition, it meets the requirements of the S6-35 / S6-45 manual transmissions used by BMW and Mercedes Benz.

RAVENOL PDK Fluid guarantees maximum wear protection in all operating conditions.

Application Notes

RAVENOL PDK Fluid has been developed especially for use in Dual Clutch Gears from Porsche.

TransmiTorque Application ssion

7DT-45 500 Nm Porsche 911
HL

7DT-45 500 Nm Porsche 911
HLA 4-Wheel-Drive

7DT-45 500 Nm Porsche Boxster
FL and Cayman

7DT-70 780 Nm Porsche 911
HLA Turbo

7DT-75 500/780 Nm Porsche
Panamera



7DT-75 500/780 Porsche
A Nm Panamera
4-Wheel-Drive

Characteristics

RAVENOL PDK Fluid offers:

- Very good lubrication even at low temperatures in winter
- High, stable viscosity index
- Very good oxidation stability
- Extensive protection against wear, corrosion and foaming
- Excellent friction coefficient
- High thermal and oxidative stability
- Excellent cooling performance

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	844	EN ISO 12185
Colour		yellow	visual
Pourpoint	°C	-63	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 22. August 2019