



## RAVENOL Vakuumpumpenöl ISO VG 32



**ART.-NR. 1330704**

1 L | 1330704-001  
5 L | 1330704-005  
10 L | 1330704-010  
20 L | 1330704-020  
20 L | 1330704-B20  
1000 L | 1330704-700

**SPECIFICATIONS** LEYBOLD-HERAEUS 175, EDWARDS ULTRAGRADE 19, ALCATEL 100, 119 UND 120 |PVR ROTANT, BECKER VAKUUMPUMPEN, HYVAC 93055, ULVAC 100, BUSCH VM UND VMH |BALZERS P3, KINNEY TYPE A, BECKMANN 19, FISHERBRAND 19, SAVANT SPO-1

**RAVENOL Vakuumpumpenöl ISO VG 32** is optimum alloyed and high level performance industrial oil with a wide range of applications throughout the industry. It is characterized by good viscosity-temperature behavior, high resistance to aging and reliable corrosion protection.

Effective additives ensure even under extreme loads an excellent wear protection. Neutral behavior to sealing materials.

## Application Notes

**RAVENOL Vakuumpumpenoel ISO VG 32** is suitable for the lubrication of vacuum pumps (rotary vane pumps, diffusion pumps, turbo pumps), where mineral oils are required, as well as for mist lubrication and crankcase.

**RAVENOL Vakuumpumpenoel ISO VG 32** oil can be used very well for the lubrication of crankcases.

## Classifications

RAVENOL Vakuumpumpenöl ISO VG 32 is tried and tested for aggregates specifying:

## Characteristics

**RAVENOL Vakuumpumpenöl ISO VG 32 offers:**

- High performance level
- Very good viscosity-temperature behavior
- High resistance to aging
- Excellent wear protection
- Reliable corrosion protection
- Neutral to seal materials



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	856	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm <sup>2</sup> /s	5,8	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	33,2	DIN 51 562
Viscosity index VI		120	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flash point (COC)	°C	220	DIN ISO 2592
FZG-Test A/8,3/90 damage loading step		12	DIN 51 354

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 13. June 2019