



## RAVENOL Getriebeöl CLP 220



ART.-NR. 1332109

5 L | 1332109-005  
20 L | 1332109-020

**SPECIFICATIONS** DIN 51 517 PART 3

**RECOMMENDATIONS** US STEEL 224 | AGMA 9005-D94 | CINCINNATI MILACRON | CLEAN PANEL COKER | S-200 OXIDATION TUBES

**RAVENOL Getriebeöl CLP 220** is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

**RAVENOL Getriebeöl CLP 220** has a low pour point and therefore a very good cold behaviour.

## Application Notes

**RAVENOL Getriebeöl CLP 220** can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

## Classifications

**RAVENOL Getriebeöl CLP 220** is tried and tested for aggregates specifying:

## Characteristics

**RAVENOL Getriebeöl CLP 220** offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	888	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm <sup>2</sup> /s	18,4	DIN 51 562
Viscosity at 20°C	mm <sup>2</sup> /s	207,6	DIN 51 562
Viscosity index VI		98	DIN ISO 2909
Pourpoint	°C	-9	DIN ISO 3016
Flash point (COC)	°C	252	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. August 2016