



RAVENOL TEG 10W-40



VISCOSITY 10W-40
SPECIFICATIONS API CF
FABRICATION SEMI-SYNTHETIC

RAVENOL TEG 10W-40 is high performance semi-synthetic multi-grade engine oil, based on hydrocrack base oils and PAO, suitable for the lubrication of natural gas engines. It has excellent lubricating film adhesion, very good shear stability and an excellent cleaning power and high resistance to aging.

ART.-NR. 1132100

1 L | 1132100-001
4 L | 1132100-004
5 L | 1132100-005
10 L | 1132100-010
20 L | 1132100-020
20 L | 1132100-B20
60 L | 1132100-060
60 L | 1132100-D60
208 L | 1132100-208
208 L | 1132100-D28
1000 L | 1132100-700

Application Notes

RAVENOL TEG 10W-40 is suitable to apply as a multi-grade engine oil for natural gas engines.

Classifications

RAVENOL TEG 10W-40 is approved, tried and tested for aggregates specifying:

Characteristics

RAVENOL TEG 10W-40 offers:

- High wear protection
- Fuel savings through low-friction properties
- Excellent detergent and dispersant properties
- Avoids the formation of accumulations of mud (black sludge)
- Longlife service due to high oxidation stability
- Excellent cold start performance
- Very good viscosity-temperature behavior
- Low evaporation loss



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	862	EN ISO 12185
Colour		brown	visual
Viscosity at 100°C	mm ² /s	14,0	DIN 51 562
Viscosity at 40°C	mm ² /s	91,3	DIN 51 562
Viscosity index VI		157	DIN ISO 2909
Pourpoint	°C	- 36	DIN ISO 3016
Flash point (COC)	°C	238	DIN ISO 2592
TBN	mg KOH/g	10,0	ASTM D2896
Sulphated ash	%wt.	1,3	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019