



RAVENOL VMP SAE 5W-30



ART.-NR. 1111122

- 1 L | 1111122-001
- 4 L | 1111122-004
- 5 L | 1111122-005
- 8 L | 1111122-008
- 10 L | 1111122-010
- 20 L | 1111122-020
- 20 L | 1111122-B20
- 60 L | 1111122-060
- 60 L | 1111122-D60
- 208 L | 1111122-208
- 208 L | 1111122-D28
- 1000 L | 1111122-700

VISCOSITY 5W-30

SPECIFICATIONS API SN | ACEA C3

FABRICATION FULLY SYNTHETIC

APPROVALS BMW LONGLIFE-04 | MB-APPROVAL 229.51 | PORSCHE C30 | VW 507 00 | VW 507 00

RECOMMENDATIONS BMW/MINI 83 21 0 398 508 | AUDI MOTORSPORT V31 748 026 | AUDI/VOLKSWAGEN G 052 195 M6 | AUDI/VOLKSWAGEN G 052 195 M4 | AUDI/VOLKSWAGEN G 052 195 M2 | MB 229.31 | FIAT 9.55535-S1 | BMW 83 21 0 398 507 | MERCEDES BENZ 000 989 89 01 10 | CHRYSLER MS-11106 | MB 000 989 89 01 10

RAVENOL VMP SAE 5W-30 is a PAO (Polyalphaolefin) based, fully synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil to be lubricated faster, thereby minimizing friction while keeping the engine clean and efficient.

RAVENOL VMP SAE 5W-30 is based on additives with reduced ash content for use in modern passenger car with diesel and gasoline engines with excellent cold start characteristics, low oil consumption and reduced pollutant emissions. This oil will increase the DPF and TWC life. Developed for fuel economy and energy conserving in EURO VI, EURO V and EURO IV Standard engines with normal and extended oil change intervals (until 50.000 km or 2 years possible).

RAVENOL VMP SAE 5W-30 achieved by its formulation with special base oils a high viscosity index. The excellent cold start behaviour ensures a optimal lubrication safety in the cold running phase.

Due to a significant fuel economy **RAVENOL VMP SAE 5W-30** contributes by reduction of emissions to conservation the environment. Minimal wear extends the lifespan of the engine.

RAVENOL VMP SAE 5W-30 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

Suitable for extended oil change intervals where recommended by manufacturer.



Application Notes

RAVENOL VMP SAE 5W-30 is a universal fuel economy, especially collected engine oil for modern gasoline and diesel engines with and without turbo charger in passenger cars and vans with extended oil change intervals. Extend the lifespan of the particle filter. Due to the specific composition is **RAVENOL VMP**

SAE 5W-30 excellent suitable for use for several of the latest OEM requirements.

Characteristics

RAVENOL VMP SAE 5W-30 offers:

- Fuel economy in part and full power operation
- MID SAPS = reduced Sulphated ash, Phosphor and Sulfur
- Excellent wear protection and high viscosity index also under high-speed driving conditions, the long life of the engine
- Excellent cold starting characteristics also at low temperatures
- A safe lubricant film at high operating temperatures
- Low evaporative tendency, so lower oil consumption
- No deposits in combustion chambers, in the piston ring zone and valves because of oil conditioned
- Neutrality towards sealing materials
- Extended oil change intervals to protect natural resources

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	853,0	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm ² /s	11,5	DIN 51 562
Viscosity at 40°C	mm ² /s	68,2	DIN 51 562
Viscosity index VI		164	DIN ISO 2909
HTHS at 150°C	mPa*s	3,6	ASTM D5481
CCS Viscosity at -30°C	mPa*s	4230	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35°C	mPa*s	13.200	ASTM D4684
Pourpoint	°C	-60	DIN ISO 3016
Noack Volatility	% M/M	7,2	ASTM D5800/b
Flash point	°C	238	DIN ISO 2592



Property	Unit	Data	Audit
Sulfated ash	%/KOH/g	0,8	AST 5152896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 28. November 2019